TECHNICAL INFORMATION

ANTI-STAINS AQUA

DESCRIPTION:

Odourless water-based paint for stains isolations, very short lapse time between application and utilization of the painted areas such as restaurants, offices, kitchens, bathrooms, hotels, public buildings, etc.

Features:

- Solvents free.
- High coverage.
- Isolate and cover stains of nicotine, smoke, grease, tannins, markers, etc.
- Excellent levelling and brushability.
- Eco friendly.
- Odourless.

TECHNICAL DATA:

Fixed vehicle	Specials resins.	
Colour	White.	
Gloss	Matt.	UNE-EN ISO 2813
Solids by weight	60 %	UNE-EN ISO 3251
Solids by volume	33 %	UNE 48090
Viscosity	105 – 110 KU (23 ± 2 ºC)	UNE 48076
Specific weight	1.35 – 1.45 Kg./l (23 ± 2 ºC)	UNE-EN ISO 2811-1
pH	< 8.0 (23 ± 2 ºC)	UNE-EN ISO 787-9
Theoretical spreading rate	10 – 14 m^2/l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	70 – 100 microns wet; 23 – 33 microns dry per coat. Apply 2 coats as finish.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Water.	
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007

EU limit value for this product (cat. A/g): 30 g/l (2010). Max. content VOC: 3 g/l

APLICATION:

Isolating paint for stains of nicotine, grease, smoke, etc. Adequate for restaurants, offices, kitchens, bathrooms, hotels, public buildings, etc. Eco friendly and odourless.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com

TECHNICAL INFORMATION

ANTI-STAINS AQUA



INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.
Thinner and cleaning utensils: Water.

- Remove the dust and the paint in bad conditions and apply a first coat diluted 5% with water. After 6 hours apply the second coat no diluted. Apply a top coat of the product desired as finishing.
- Consolidate and fix sandy supports with DECOKRIL PENETRATING.
- If there is fungus or algae formation clean previously.

In general we recommend:

- Apply between 5 °C and 35 °C.
- It is not recommended to apply in full sun or high temperatures of the surface.
- Perfectly mix the product before use.
- In case of contamination by fungus or algae:
  - Wash with a solution of water and bleach to 10%.
  - Rinse with water.
  - Let dry completely before beginning to paint.
  - Use products with protection against FUNGUS.
- In case of presence of saline efflorescence:
  - Brush and wash with hydrochloric acid diluted to 10% with water.
  - Rinse with water.
  - Let dry completely before beginning to paint.

PRESENTATION:

Plastic packaging of: 0.750 Litres; 4 Litres; 15 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com