



TECHNICAL INFORMATION

DECO-METALLIC



DESCRIPTION:

Acrylic enamel metallic effect of high performance for decoration and protection of metal surfaces, wood, plaster, timberworks, obtaining a metallic effect.

Features:

-) Excellent adherence on substrates of ferrous and non ferrous metal (iron, galvanized steel, etc.), wood, plaster, etc.
-) High outdoor durability.
-) Water resistant to corrosion and weathering.
-) High hardness, resistance to scratch and shock.
-) Resistant to chemicals.
-) Excellent leveling and brushability.

TECHNICAL DATA:

Fixed vehicle	Acrylic resin.	
Colour	Gold 300, Copper 310, Silver 320.	
Gloss	Satin.	
Solids by weight	37 %	UNE-EN ISO 3251
Solids by volume	22 %	UNE 48090
Viscosity	55 – 65 KU (23 ± 2 °C)	UNE 48076
Specific weight	0.85 – 0.95 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
Theoretical spreading rate	16 – 20 m ² /l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	50 – 60 microns wet; 10 – 14 microns dry per coat. Apply 2 coats as finish.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	12 – 24 hours.	
Solvent	Aromatic solvent.	
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007

EU limit value for this product (cat. A/i): 500 g/l (2010). Max. content VOC: 490 g/l

APLICACION:

Decoration and surface protection of iron/steel, wood, plaster, timber works etc., indoors and outdoors, where is desired a metallic effect finish.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

DECO-METALLIC



INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.
Thinner and cleaning utensils: ACRYLIC SOLVENT.

Product ready for use DO NOT DILUTE.

Painted surfaces must be dry and clean of dust, rust, grease, etc. and primed properly.

) Unpainted surfaces:

- Iron, steel, galvanized steel: Prime with PRIMER POLYVALENT if you need an anti-corrosion effect. Apply two coats of DECO-METALLIC for finish.
- Plaster, cement, wood: Prime with SEALER DECOLOR. Apply two coats of DECO-METALLIC for finish.

) Painted surfaces:

- If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
- If the paint is in good condition, sand and apply two coats of DECO-METALLIC for finish.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Metal packaging of: 0.250 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>