



TECHNICAL INFORMATION

DECOKRIL WATERPROOFING W



DESCRIPTION:

Transparent waterproofing liquid for protecting exterior surfaces, reducing in a durable way the penetration of water no modifying the original aspect of the support. Can be apply over concrete, mortar, brick, natural stone, fibre cement, etc.

Features:

-) Reduce algae, fungus and efflorescence formation.
-) Breathable.
-) Waterproofing.
-) No modify the original aspect of the surface.
-) Eco friendly.
-) Odourless.
-) Ready for use.

TECHNICAL DATA:

Chemical composition	Water based emulsion of silanes and siloxanes.	
Appearance	Milky, white, liquid	
Specific weight	0.95 – 1.05 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
Theoretical spreading rate	6 – 8 m ² /l. Take in mind application leaking, surface irregularities, etc.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	3 – 4 hours.	
Solvent	Water.	

EU limit value for this product (cat. A/h): 30 g/l (2010). Max. content VOC: 0 g/l

APLICACION:

Transparent waterproofing liquid for protecting exterior surfaces, reducing in a durable way the penetration of water no modifying the original aspect of the support. Can be apply over concrete, mortar, brick, natural stone, fibre cement, etc. Reduce algae, fungus and efflorescence formation.

INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.
Cleaning utensils: Water.

Surfaces to be painted must be dry and clean of dust, grease, oxide, efflorescence, etc.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com <http://www.decolor.com>



TECHNICAL INFORMATION

DECOKRIL WATERPROOFING W



Take in mind that once applied the product must avoid rain water.

Employ the product as it is over all the surface, no dilute the product.

After raining wait until 24 hour to apply the product, in case of high pressure water cleaning waits 72 hours.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.
-) Test the product before the complete application.

PRESENTATION:

Plastic packaging of: 0,750 Litres; 5 Litres; 10 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>