# TECHNICAL INFORMATION

# DECOKRIL PIGMENTED




## DESCRIPTION:

Water-based pigmented primer for all types of masonry substrates.

Features:

- Excellent adhesion to concrete.
- Excellent alkali and efflorescence resistance.
- Excellent water resistance.
- Exterior and interior.
- Eco friendly.
- Solvents free.
- Ready for use, do not dilute.

## TECHNICAL DATA:

| | | |
|---|---|---|
| Fixed vehicle | Acrylic copolymer. | |
| Colour | White. | |
| Specific weight | 1.25 – 1.35 Kg./l (23 ± 2 ºC) | UNE-EN ISO 2811-1 |
| pH | > 8.5 (23 ± 2 ºC) | UNE-EN ISO 787-9 |
| Theoretical spreading rate | 10 – 15 $m^2$/l. Take in mind application leaking, surface irregularities, etc. | |
| Total drying | 30 – 60 minutes. | UNE 48301 |
| Repaint | 4 hours. | |
| Solvent | Water. | |

EU limit value for this product (cat. A/h): 30 g/l (2010). Max. content VOC: 0 g/l

## APLICATION:

Primer for concrete or mortar, improving the adhesion of the subsequent layers with high resistance to alkalis and efflorescence both indoors and outdoors. Suitable product as basement waterproofing sealer and primer for fibre cement.

## INSTRUCTIONS FOR USE:

Application methods: Brush, roller or spray.
Cleaning utensils: Water.

Ready for use, do not dilute.

Painted surfaces must be dry and clean of dust, rust, grease, etc.

**Pinturas Decolor**
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com

# TECHNICAL INFORMATION

## DECOKRIL PIGMENTED

- Unpainted surfaces:
  - Dead or powdery plaster, cement, brickwork: Fix the surface with DECOKRIL PIGMENTED. Once is dry apply the coat that you want as a finishing.
- Painted surfaces:
  - If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
  - If the paint is in good conditions wash, sand and fix the surface to be painted with DECOKRIL PIGMENTED. Once is dry applying the coat that you want as a finishing.

In general we recommend:

- Apply between 5 °C and 35 °C.
- It is not recommended to apply in full sun or high temperatures of the surface.
- Perfectly mix the product before use.
- In case of contamination by fungus or algae:
  - Wash with a solution of water and bleach to 10%.
  - Rinse with water.
  - Let dry completely before beginning to paint.
  - Use products with protection against FUNGUS.
- In case of presence of saline efflorescence:
  - Brush and wash with hydrochloric acid diluted to 10% with water.
  - Rinse with water.
  - Let dry completely before beginning to paint.

## PRESENTATION:

Plastic packaging of: 10 Litres

## STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

## ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

**Pinturas Decolor**
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com