



TECHNICAL INFORMATION

DECOKRIL RAPID



DESCRIPTION:

Water-based pigmented primer for all types of masonry substrates. Suitable even on fresh concrete and mortar.

Features:

-) Excellent adhesion to concrete.
-) Excellent alkali and efflorescence resistance.
-) Excellent water resistance.
-) Good UV resistance.
-) Exterior and interior.
-) Eco friendly.
-) Solvents free.
-) Ready for use, do not dilute.

TECHNICAL DATA:

Fixed vehicle	Acrylic copolymer.	
Colour	White.	
Specific weight	1.30 – 1.40 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	> 8.5 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	10 – 12 m ² /l. Take in mind application leaking, surface irregularities, etc.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	4 hours.	
Solvent	Water.	

EU limit value for this product (cat. A/h): 30 g/l (2010). Max. content VOC: 0 g/l

APPLICATION:

Primer for fresh concrete («green») or mortar, improving the adhesion of the subsequent layers with high resistance to alkalis and efflorescence both indoors and outdoors. Suitable product as basement waterproofing sealer and primer for fibre cement.

INSTRUCTIONS FOR USE:

Application methods: Brush, roller or spray.

Cleaning utensils: Water.

Ready for use, do not dilute.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

DECOKRIL RAPID



Painted surfaces must be dry and clean of dust, rust, grease, etc.

) Unpainted surfaces:

- Dead or powdery plaster, cement, brickwork: Fix the surface with DECOKRIL RAPID. Once is dry apply the coat that you want as a finishing.

) Painted surfaces:

- If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
- If the paint is in good conditions wash, sand and fix the surface to be painted with DECOKRIL RAPID. Once is dry applying the coat that you want as a finishing.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.
-) In case of contamination by fungus or algae:
 - Wash with a solution of water and bleach to 10%.
 - Rinse with water.
 - Let dry completely before beginning to paint.
 - Use products with protection against FUNGUS.
-) In case of presence of saline efflorescence:
 - Brush and wash with hydrochloric acid diluted to 10% with water.
 - Rinse with water.
 - Let dry completely before beginning to paint.

PRESENTATION:

Plastic packaging of: 10 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>