



TECHNICAL INFORMATION

IBIZA DECORATIVE COSTA

DESCRIPTION:

Metalized water paint of maximum performance and high content of metallic pigments that allows a simple application to achieve innumerable innovative effects with high quality finishes.

Features:

-) Fast drying.
-) Excellent leveling and brushability.
-) Very washable, great hardness, scratch resistance and shock.
-) Resistant to blocking.
-) Exterior and interior.
-) Excellent durability to the exterior.
-) Without smell.
-) Environmentally friendly.

TECHNICAL DATA:

Fixed vehicle	Acrylic resins.	
Colour	Gold, Silver, White.	
Specific weight	1.00 – 1.10 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	> 8.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	12 – 16 m ² /l. Take in mind application leaking, surface irregularities, etc.	
Total drying	2 hours.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Water.	

EU limit value for this product (cat. A/k): 100 g/l (2010). Max. content VOC: 5 g/l

APPLICATION:

Metallized water paint with maximum performance and high content of metallic pigments. Product with maximum washability, hardness and adhesion.

Ideal for kitchens and bathrooms, passage areas, exteriors, any metal surface, wood, etc.

INSTRUCTIONS FOR USE:

Application methods: Brush, roller, gun, blade, sponge, spatula.

Thinner and cleaning of tools: Water.

Painted surfaces must be dry and clean of dust, rust, grease, etc. and primed properly.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

IBIZA DECORATIVE COSTA

1. Substrate preparation

- Iron, steel: Prime with AQUA POLYVALENT PRIMER.
- Plaster, cement: Prime with DECOKRIL PENETRANTE.
- Wood: Prime with AQUA SEALANT.

2. Application

Perfectly homogenize the product before use.

-) With airless gun: Dilute with a maximum of 10% water and apply with a fine nozzle.
-) With enameling roller: Apply 2 layers crosswise to disguise the roller strokes.
-) With pallet or spalter: Apply with wrist turns.
-) With sponge or spatula: Apply directly with sponge or spatula on any type of smooth, rough or textured surface.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Plastic packaging of: 1 L.

STORAGE:

12-24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.