



TECHNICAL INFORMATION

PAILLETES DECORATIVE COATINGS

DESCRIPTION:

PAILLETES is a decorative and durable coating, which is obtained by blowing the scales on a delayed-drying paint base. Once dried, the flakes are covered with a transparent varnish. Mixing scales of different sizes, flakes and colours can create a multitude of effects.

PAILLETES are decorative products to cover walls and / or floors.

PAILLETES is easy to apply, very resistant and adapts perfectly to a modern design and environment.

TECHNICAL DATA:

Theoretical spreading rate	PAILLETES : 180 gr./m ² . Consideration should be given to application losses, surface irregularities, etc.
----------------------------	--

APPLICATION:

PAILLETES are decorative products to cover walls and / or floors.

INSTRUCTIONS FOR USE:

Application methods: Flakes projection system or sprinkle manually.

1. Substrate preparation

It can be used over any kind of support, painted surfaces, plaster, plasterboard walls, walls with plaster or cement plaster, etc.

Surfaces should be dry and free of dust, rust, grease, etc. and primed properly with SELLADORA, SELLADORA AQUA, DECOKRILL PENETRANTE, or DECOKRIL.

In areas with poor adherence (powdery walls, surfaces with little pore, etc.) Should be applied initially DECOKRIL PENETRANTE to increase the adherence.

On floors previously apply DECO-EPOXY 3D.

It is generally recommended:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply elevated temperatures support.
-) Perfectly homogenize the product before use.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

PAILLETES DECORATIVE COATINGS

2. Application

Walls:

Apply the first coat SPECIAL SATIN o POLIMUL 202, on properly prepared walls, with a roller of medium (12 mm) hair paint to $\pm 8\text{m}^2/\text{l}$.

Apply on the wet surface, blowing with the PAILLETES projector.

Floors:

Floors: Apply the first layer DECO-EPOXY 3D.

Apply to wet surface, PAILLETES until saturated.

3. Finishing

Walls:

When the first coat is dry (12 hours), apply with a VARNISH INTERIOR AQUA lacquer roller at $\pm 10\text{-}12\text{ m}^2/\text{l}$.

Floors:

On floors apply as DECO-EPOXY 3D termination.

PRESENTATION:

Plastic packaging of: 2 Kg.

STORAGE:

12-24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>