



TECHNICAL INFORMATION

MATT PAINT ANTI-INSECT

DESCRIPTION:

Matt paint of high quality with insecticide, killing by contact flies, mosquitoes, bees, spiders, ants, etc. can be used for the protection and decoration of interior and exterior surfaces.

“The commercialization of this product is only for export and use outside the European Union”

Features:

-) Odourless, rooms can be used just painted.
-) Great power opacity and whiteness.
-) Resistant to weather and sunlight.
-) Excellent levelling and brushability.
-) Insect repellent.
-) Good adhesion.
-) Tendency to leak very small.
-) Paint with protective fungicide - algaecide.
-) Fully washable last 15 days of application.

TECHNICAL DATA:

Fixed vehicle	Acrylic resin.	
Colour	White.	
Gloss	Matt. 60°: 2-3 GU	UNE-EN ISO 2813
Solids by weight	67 %	UNE-EN ISO 3251
Solids by volume	43 %	UNE 48090
Viscosity	115 – 120 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.50 – 1.60 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	8.0 – 10.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	11 – 15 m ² /l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	65 – 90 microns wet; 30 – 40 microns dry per coat. Apply 2 coats as finish.	
Total drying	1 hour.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Water.	
Wet scrub resistance	Class 2 ($\geq 5 \text{ } \uparrow\text{m}$ and $< 20 \text{ } \uparrow\text{m}$ for 200 wet scrub UNE-EN ISO 11998)	UNE-EN 13300
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007

EU limit value for this product (cat. A/a): 30 g/l (2010). Max. content VOC: 0 g/l

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

MATT PAINT ANTI-INSECT

APPLICATION:

Decoration of Interior and exterior where you want to apply a paint with insecticide character and without smell, no hassles, no health risks for the immediate use of the rooms. Ideal for schools, hospitals, occupied dwellings, etc.

INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.

Thinner and cleaning utensils: Water.

Painted surfaces must be dry and clean of dust, rust, grease, etc. and primed properly. PRIMING COAT IS VERY IMPORTANT.

) Unpainted surfaces:

- Gypsum, cement and lime: Apply a first coat diluted 15% with water or prime with PENETRATING DECOKRIL. Apply two coats of ANTI-INSECT MATT diluted to 5% with water for finish.
- Iron, steel: Prime with PRIMER POLYVALENT AQUA. Apply two coats of ANTI-INSECT MATT diluted to 5% with water for finish.
- Wood: Prime with SEALER AQUA. Apply two coats of ANTI-INSECT MATT diluted to 5% with water for finish.
- "Dead" or powdery plaster: Prime with PENETRATING DECOKRIL. Apply two coats of ANTI-INSECT MATT diluted to 5% with water for finish.

) Painted surfaces:

- If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
- If the paint is in good condition, wash and sand and apply ANTI-INSECT MATT.

If you want to colour it can be used DECOLOR WATER COLORANT or DECOLOR UNIVERSAL COLORANT, at most 5%.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.
-) In case of contamination by fungus or algae:
 - Wash with a solution of water and bleach to 10%.
 - Rinse with water.
 - Let dry completely before beginning to paint.
 - Use products with protection against FUNGUS.
-) In case of presence of saline efflorescence:

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

MATT PAINT ANTI-INSECT

- Brush and wash with hydrochloric acid diluted to 10% with water.
- Rinse with water.
- Let dry completely before beginning to paint.

PRESENTATION:

Plastic packaging of: 4 Litres; 14 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>