



TECHNICAL INFORMATION

WOODXYL F&I AQUA



DESCRIPTION:

WOODXYL F&I AQUA is a wood protector, water-based, ready-to-use, exerting a preventive function against wood destroying fungi (brown rot: *Gloeophyllum trabeum*, *Coniophora puteana*, *Poria placenta*) and blueberry fungi (*Aureobasidium pullulans* spp, *Sclerophoma pithyophilla*). WOODXYL F&I AQUA also has a preventive function against insects like house longhorn beetle (*Hylotrupes bajulus* L.) and termites (*Reticulitermes* sp.).

Direct contact with soil and aquatic environment should be avoided.

Features:

-) Colourless water-based preventive treatment for wood.
-) Colourless primer and primer, with preventive efficacy against xylophagous insects, woodworms and termites.
-) Recommended for interior and exterior wood carpentry that need to be protected against xylophagous insects (woodworms and termites), rot and bluish fungi and the eradication of larval xylophagous insects (woodworms) in interior wood.
-) Product registration number: ES/MR(NA)-2017-08-00461

TECHNICAL DATA:

Fixed vehicle	Alkyd resin.	
Colour	Colourless.	
Specific weight	0.95 – 1.05 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	>8.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Dosage levels	200 ml/m ²	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	24 hours.	
Solvent	Water.	

EU limit value for this product (cat. A/e): 130 g/l (2010). Max. content VOC: 65 g/l

APPLICATION:

WOODXYL F&I AQUA is intended for treating exterior woods such as windows, exterior doors, siding, fences, eaves and sheds.

INSTRUCTIONS FOR USE:

Application methods: brush or roller.

Cleaning utensils: Water.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

WOODXYL F&I AQUA



Painted surfaces must be dry, sanded and clean of dust, rust, grease, etc.

The target end-use market is DIY and professional, suitable for use Class 2 and 3 use according to EN 335:2013.

-) New woods: For a preventive action, apply the product with a brush until reaching the recommended dose.
-) Varnished and painted wood: Total removal of old layers of paint.

The treated wood must be repainted for outdoor use, following the recommendations for use of such product.

The wood highly resinous must be cleaned previously with SYNTETIC AND GREASE SOLVENT, UNIVERSAL SOLVENT or ODOURLESS SOLVENT, to avoid problems during the drying.

In general, we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Plastic packaging of:

General public: 0,750 Litres; 2,5 Litres
Specialized professional staff: 20 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com <http://www.decolor.com>