TECHNICAL INFORMATION

PROTECTIVE WAX OF STUCCOS

DESCRIPTION:

Synthetic wax to protect the stucco and increase its gloss.

Characteristics:

- Easy to apply.
- Transparent.
- Improves resistance to wear, rubbing and grating.
- Excellent gloss level.
- Hydrofugation of the support.

TECHNICAL DATA:

Fixed vehicle	Synthetic wax	
Appearance	White paste	
Specific weight	0.75 – 0.85 Kg./. (23 ± 2 ºC)	UNE-EN ISO 2811-1

EU limit value for this product (cat. A/l): 200 g/l (2010). Max. content VOC: 200 g/l

APPLICATION:

Synthetic wax to protect the stucco and increase its gloss.

INSTRUCTIONS FOR USE:

Application methods: Spatula.
Cleaning utensils: Water.

1. Preparation of the support

Prior preparation is not necessary, only 48 hours have elapsed since the application of DECO-ESTUC.

In general we recommend:

- Apply between 5 °C and 35 °C.
- It is not recommended to apply in full sun or high temperatures of the surface.
- Perfectly mix the product before use it.

2. Preparation of the product

Do not dilute product. The product is served ready to use.
Thoroughly homogenize the product before use.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com

TECHNICAL INFORMATION

PROTECTIVE WAX OF STUCCOS

3. Application and finishing.

Extend the product with a cross-shaped spatula, with a yield of 6 - 10 g/m^2.

After 2 hours of drying, the surface should be polished with a lint-free cotton cloth. It is important to wait before polishing, the film should be dry and not sticky.

Depending on the desired brightness repeat the steps in step 3.

PACKAGING:

Plastic packaging of: 0.750 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor
Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com http://www.decolor.com