



TECHNICAL INFORMATION

D-800 MATT PAINT



DESCRIPTION:

High quality acrylic-polyurethane paint for the protection and decoration of interior and exterior ceilings and walls.

Characteristics:

-) Perfectly homogeneous finish.
-) Long open time - no trace of roller, guaranteeing the absence of traces.
-) 2 in 1: Primer + finish.
-) High covering and deep matt.
-) Non-spattering.
-) Breathable and waterproof.
-) Resistant to weather and sunlight.
-) Resistant to alkaline substrates.
-) Good adherence.
-) Washable 15 days after applied.

TECHNICAL DATA:

Fixed vehicle	Copolymer acrylic + PU.	
Colour	White. Tinting system DECO-COLOR.	
Gloss	Matt. 85°: <1 GU	UNE-EN ISO 2813
Solids by weight	61 %	UNE-EN ISO 3251
Solids by volume	46 %	UNE 48090
Viscosity	126 – 130 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.35 – 1.45 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	8.0 – 10.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	8 m ² /l. Take in mind application leaking, surface irregularities, etc.	
Total drying	1 hour.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Water.	
Wet scrub resistance	Class 1	UNE-EN 13300
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007
Emissions in the indoor air	Class A+	French Legislation Decree No. 2011-321 of March 23, 2011

EU limit value for this product (cat. A/c): 40 g/l (2010). Max. content VOC: 15 g/l

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

D-800 MATT PAINT



APPLICATION:

Paint for the protection and decoration of indoors and outdoors with a deep matt finish of high quality and beautiful. Suitable for plaster ceilings and walls, cement plastered walls and masonry in general. It is ideal for painting exterior facades as it is breathable and waterproof.

INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.
Thinner and cleaning utensils: Water.

Painted surfaces must be dry and clean of dust, rust, grease, etc. and primed properly.

) Unpainted surfaces:

- Gypsum, cement and lime: Apply two coats of D-800 MATT diluted to 5% with water for finish.
- Iron, steel: Prime with PRIMER POLYVALENT AQUA. Apply two coats of D-800 MATT diluted to 5% with water for finish.
- Wood: Prime with SEALER AQUA. Apply two coats of D-800 MATT diluted to 5% with water for finish.

) Painted surfaces:

- If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
- If the paint is in good condition, wash and sand and apply D-800 MATT.
- If there is fungus or algae formations clean previously.

If you want to colour it can be used DECOLOR WATER COLORANT or DECOLOR UNIVERSAL COLORANT, at most 5%.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.
-) In case of contamination by fungus or algae:
 - Wash with a solution of water and bleach to 10%.
 - Rinse with water.
 - Let dry completely before beginning to paint.
 - Use products with protection against FUNGUS.
-) In case of presence of saline efflorescence:
 - Brush and wash with hydrochloric acid diluted to 10% with water.
 - Rinse with water.
 - Let dry completely before beginning to paint.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54
E-mail: dptotecnico@decolor.com <http://www.decolor.com>



TECHNICAL INFORMATION

D-800 MATT PAINT



PRESENTATION:

Plastic packaging of: 4 Litres; 14 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>