



TECHNICAL INFORMATION

SEALING AQUA



DESCRIPTION:

High quality water sealer made from special resins for the preparation of wood surfaces, plaster and other porous substrates.

Features:

-) Improve de adherence.
-) Good filling and sealing power improving the finish quality.
-) Fast drying.
-) Exterior and interior.
-) Easy sanding.
-) Sandable after 6 hours.
-) Eco friendly.
-) Odourless.

TECHNICAL DATA:

Fixed vehicle	Resins specials.	
Colour	White.	
Gloss	Matt.	UNE-EN ISO 2813
Solids by weight	60 %	UNE-EN ISO 3251
Solids by volume	46 %	UNE 48090
Viscosity	90 – 100 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.30 – 1.40 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	> 8.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	10 – 14 m ² /l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	70 – 100 microns wet; 32 – 46 microns dry per coat. Apply 2 coats as finish.	
Total drying	2 – 3 hours.	UNE 48301
Repaint	6 hours.	
Solvent	Water.	
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007

EU limit value for this product (cat. A/g): 30 g/l (2010). Max. content VOC: 15 g/l

APLICACION:

Water sealer of surfaces of wood, plaster and other porous substrates, both indoors and outdoors. To prepare and cover brackets funds before the finishing products. Eco-friendly and odourless.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

SEALING AQUA



INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.
Thinner and cleaning utensils: Water.

Painted surfaces must be dry and clean of dust, rust, grease, etc.

Sand the surface before applying the SEALING AQUA and remove the dust.

Apply the SEALING AQUA on the surface to be treated diluted with 5% with water and let dry. After 6 hours, sand gently and remove dust. Apply the second layer later and let it dry. Finally, sand lightly and apply the finishing product.

If you want to colour it can be used DECOLOR WATER COLORANT or DECOLOR UNIVERSAL COLORANT, at most 5%.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Plastic packaging of: 0.750 Litres; 4 Litres

STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>