



TECHNICAL INFORMATION

ANTI-STAINS



DESCRIPTION:

Fast drying isolation paint for stains very short lapse time between application and utilization of the painted areas such as restaurants, offices, kitchens, bathrooms, hotels, public buildings, etc.

Features:

-) Excellent adherence.
-) High coverage.
-) Covering power over stains of grease, smoke, nicotine, etc.
-) Excellent leveling and brushability.

TECHNICAL DATA:

Fixed vehicle	Alkyd resins.	
Colour	White.	
Gloss	Matt.	UNE-EN ISO 2813
Solids by weight	76 %	UNE-EN ISO 3251
Solids by volume	59 %	UNE 48090
Viscosity	100 – 106 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.45 – 1.55 Kg./l (23 ± 2 °C)	UNE-EN ISO 2811-1
Theoretical spreading rate	10 – 14 m ² /l and coat. Take in mind application leaking, surface irregularities, etc.	
Recommended thickness	70 – 100 microns wet; 41 – 59 microns dry per coat. Apply 2 coats as finish.	
Total drying	1 – 2 hours.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Aromatic hydrocarbons.	

EU limit value for this product (cat. A/g): 350 g/l (2010). Max. content VOC: 350 g/l

APPLICATION:

Isolation coating for stains of nicotine, greases, smoke, etc. Perfect for restaurants, offices, hotels, kitchens, bathrooms, etc.

INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.

Thinner and cleaning utensils: ACRYLIC SOLVENT or UNIVERSAL SOLVENT.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

ANTI-STAINS



Apply a first coat diluted 5 – 10% with ACRYLIC SOLVENT or UNIVERSAL SOLVENT. After that apply 1 or 2 coats of ANTI-STAINS none diluted, you can use other product as top coat finishing.

If you want to colour it can be used DECOLOR UNIVERSAL COLORANT, at most 5%.

In general we recommend:

-) Apply between 5 °C and 35 °C.
-) Perfectly mix the product before use.

PRESENTATION:

Metallic packaging of: 0.750 Litres; 4 Litres

STORAGE:

24 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>