



TECHNICAL INFORMATION

KITCHENS AND BATHROOMS



DESCRIPTION:

Multi-purpose paint waterborne for paint on glass, tiles, ceramic, PVC, wood, galvanized steel, aluminium, some plastic, etc. 2-in-1 paint, no primer required on a wide variety of surfaces. Paint with protection against fungi and algae.

Features:

-) Excellent adherence on critical surfaces (glass, tiles, ceramic, PVC, wood, galvanized steel, aluminium, some plastic, etc.)
-) Excellent water resistance.
-) No yellowish.
-) Excellent levelling and brushability.
-) Great hardness and resistant to scratches.
-) Single component.
-) Fast drying.
-) Interior and exterior
-) Eco friendly.

TECHNICAL DATA:

Fixed vehicle	Acrylic resin.	
Colour	White. Tinting system DECO-COLOR.	
Gloss	Satin G2. 60°: 15-20	UNE-EN 13300
Solids by weight	56 %	UNE-EN ISO 3251
Solids by volume	39 %	UNE 48090
Viscosity	90 – 100 KU (23 ± 2 °C)	UNE 48076
Specific weight	1.25 – 1.35 kg/l (23 ± 2 °C)	UNE-EN ISO 2811-1
pH	8.0 – 10.0 (23 ± 2 °C)	UNE-EN ISO 787-9
Theoretical spreading rate	8 – 12 m ² /l. Take in mind application leaking, surface irregularities, etc.	
Total drying	30 – 60 minutes.	UNE 48301
Repaint	4 – 6 hours.	
Solvent	Water.	
Reaction to fire	Class M-1	UNE 23727
Reaction to fire	Bs1d0	UNE-EN 13501-1:2007
Emissions in the indoor air	Class A+	French Legislation Decree No. 2011-321 of March 23, 2011

EU limit value for this product (cat. A/i): 140 g/l (2010). Max. content VOC: 0 g/l

Pinturas Decolor

Industrial Estate El Salvador Avenue 3^a, Parcels 4 and 5

02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

KITCHENS AND BATHROOMS



APPLICATION:

Water-based paint for painting kitchens and bathrooms on a wide variety of materials. Resistant to grease and damp stains. Full adhesion on ceramic substrates and vitrified surfaces.

INSTRUCTIONS FOR USE:

Application methods: brush, roller or spray.

Cleaning utensils: Water.

Painted surfaces must be dry and clean of dust, rust, grease, etc. To do this, use bleach diluted 1:8 with water, cleaning solvent or strippers.

) Unpainted surfaces:

- Glass, tile, ceramic, etc.: Apply two or three coats. It is advisable to make a test over surfaces non porous. Sand before applying to facilitate the adherence.
- General masonry: Apply two or three coats.
- Cement and concrete: First concrete must be cured for which one month must have elapsed since its application. Treat the surface with hydrochloric (hydrochloric acid) diluted 10-15% with water to neutralize the alkalinity of cement, then rinse and let dry. Apply two or three coats.
- Wood: Apply two or three coats.
- Galvanized steel, aluminium: Apply two or three coats.
- PVC and plastic: Sand before applying to facilitate the adherence. After that apply two coats. It is advisable to make a test over the plastic to check the adherence.

) Painted surfaces:

- If the paint is in poor condition, remove completely and proceed as in unpainted surfaces.
- If the paint is in good condition, sand and apply KITCHENS AND BATHROOMS.

If you want to colour it can be used DECOLOR WATER COLORANT or DECOLOR UNIVERSAL COLORANT, at most 5%.

In general, we recommend:

-) Apply between 5 °C and 35 °C.
-) It is not recommended to apply in full sun or high temperatures of the surface.
-) Perfectly mix the product before use.

PRESENTATION:

Metal packaging of: 750 ml; 4 L

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5

02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>



TECHNICAL INFORMATION

KITCHENS AND BATHROOMS



STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

Pinturas Decolor

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5

02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14

E-mail: dptotecnico@decolor.com

<http://www.decolor.com>