



## TECHNICAL INFORMATION

### DECOPLAST EXTERIOR POWDER



#### DESCRIPTION:

Micronized powder putty based on binders and mineral charges, intended for the masonry repair, plastering, cracks and levelling on cement, brick, block, concrete, etc.

It is a hygroscopic material, so it must be preserved from humid environments.

Features:

- ) Excellent open time.
- ) Exterior - interior.
- ) Easy to apply.
- ) High adherence and hardness.
- ) Good filling power.

#### TECHNICAL DATA:

|                            |                                                                                               |                 |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------|
| Colour                     | White.                                                                                        |                 |
| Theoretical spreading rate | 1.50 Kg./m <sup>2</sup> /1 mm. Take in mind application leaking, surface irregularities, etc. |                 |
| Thickness                  | 3 mm                                                                                          |                 |
| Setting time               | 4 hours                                                                                       |                 |
| Drying                     | Coat of 1 mm: 8 hours                                                                         |                 |
| Traction adherence         | > 5 Kg/cm <sup>2</sup>                                                                        | UNE-EN ISO 4824 |

#### APPLICATION:

Once the product is perfectly kneaded, we obtain a special outer putty powder to fill holes, cracks or plastering walls.

After drying, a surface of great hardness, whiteness and extraordinary adhesion, obtaining a perfect surface for subsequent painting.

#### INSTRUCTIONS FOR USE:

Application methods: trowel or spatula.  
Cleaning accessories: Water.

Surfaces must be dry and clean of dust, rust, grease, etc.

---

#### **Pinturas Decolor**

Industrial Estate El Salvador Avenue 3<sup>a</sup>, Parcels 4 and 5  
Apdo. 106 – 02630 La Roda (Albacete) Spain  
Phone: +34 967 44 17 14 Fax: +34 967 44 33 54  
E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com) <http://www.decolor.com>



## TECHNICAL INFORMATION

### DECOPLAST EXTERIOR POWDER



It is mixed with water in a percentage of 30% by weight. To achieve a good kneading, it is advisable to use a helical or special type putty mixer, putting the water first, and then the product. Then knead, this way you get an easy-to-handle paste.

After kneading it is convenient to leave it at rest for 2 or 3 minutes.

Once the product is perfectly kneaded, it is applied with a spatula or trowel.

If there are imperfections, they can be reviewed after a period of 3-4 hours from the application. If there is any missing, it can be easily sanded.

Maximum thickness per layer 3 mm.

In general, it is recommended:

- ) If a wall is partially patched, it is necessary to apply DECOKRIL RAPID or DECOKRIL PENETRATING to avoid changes in the colour tone of the paint.
- ) It can be applied directly to exterior - interior if they are hard, dry and clean (cement, paints, coatings).
- ) Do not apply on plasterboard supports.
- ) Do not wet the supports before applying.
- ) Do not beat the putty again once it begins to set.

#### PRESENTATION:

Packaging of: 5 Kg, 15 Kg

#### STORAGE:

12 months in closed original container under roof and temperatures between 5 °C and 35 °C and protected from the weather.

#### ADDITIONAL INFORMATION:

The information contained in this document serves as a guide for the user but does not constitute a guarantee. For information about safety and the environment, please refer to the Safety Data Sheet.

---

#### **Pinturas Decolor**

Industrial Estate El Salvador Avenue 3ª, Parcels 4 and 5  
Apdo. 106 – 02630 La Roda (Albacete) Spain

Phone: +34 967 44 17 14 Fax: +34 967 44 33 54

E-mail: [dptotecnico@decolor.com](mailto:dptotecnico@decolor.com)

<http://www.decolor.com>